

# T estpassport問題集



---

更に上のクオリティ      更に上のサービス

一年で無料進級することに提供する  
[Http://www.testpassport.jp](http://www.testpassport.jp)

**Exam** : **1Z0-878**

**Title** : Oracle Solaris 10 System  
Administrator Certified  
Professional Exam, Part II

**Version** : Demo

1.DRAG DROP

Place each syslogd severity level on the correct description.

Severity Level	Description
emerg	Other errors
alert	Panic conditions that are normally broadcast to all users
err	Conditions that are not errors but might require special handling
notice	Conditions that should be corrected immediately

**Answer:**

Place each syslogd severity level on the correct description.

Severity Level	Description
emerg	emerg
alert	err
err	alert
notice	notice

2.The security administrator wants to assign user bob to a netsec role so that the user can run the ifconf ig (iM) and snoop (iM) commands with a rights profile named NSM.

Which entries will be contained in the /etc/security/exec\_attr file after the required RBAC configuration has been implemented when using privileges rather than uid 0?

- A. NSM:suser:cmd:::/sbin/ifconfig:privs=sys\_net\_conf ig NSM:suser:cmd::: Aisr/sbin/snoop:privs=net\_rawaccess
- B. HSM:bob:cmd:::/sbin/ifconfig:privs=sys\_net\_config NSM:bob:cmd::: Aisr/sbin/snoop:privs=net\_rawaccess
- C. HSM:netsec:cmd:::/sbin/ifconfig:privs=sys\_net\_config NSM:netsec:cmd::: Aisr/sbin/snoop:privs=net\_rawaccess
- D. NSM:Solaris:cmd:::/sbin/ifconfig:privs=sys\_net\_config NSM:Solaris:cmd::: Aisr/sbin/snoop:privs=net\_rawaccess

**Answer: D**

3. Given the command and output:

```
# profiles -1 testrole
```

Audit Control:

```
/etc/init.d/audit uid=0, egid=3 /etc/security/bsmconv uid=0 /etc/security/bsmunconv uid=0
```

```
/usr/sbin/audit uid=0 /usr/sbin/auditconfig uid=0 /usr/sbin/auditd uid=0
```

All:

And given the fact that testrole executes commands with a profile shell, with what effective UID and real UID will the /usr/sbin/auditd program be started?

- A. effective UID 0 and real UID 0
- B. effective and real UID of testrole
- C. effective UID of testrole and real UID 0
- D. effective UID 0 and real UID of testrole

**Answer: A**

4. Given the entry from the /etc/user\_attr file:

```
User10:::profiles=User Security,Maintenance and Repair;roles=MediaAdmin;type=normal
```

Which statement is correct?

- A. The user10 account is a role account.
- B. The MediaAdmin role is defined in the /etc/security/auth\_attr file.
- C. The User Security, Maintenance and Repair profile is defined in the /etc/security/prof\_attr file.
- D. The User Security and Maintenance and Repair profiles are defined in the /etc/security/prof\_attr file.

**Answer: D**

5. On a Solaris 10 OS, you want to enable a syslog message for all incoming inetd requests.

Which command do you need to execute?

- A. inetadm - Mtcp\_trace=true
- B. inetadm - Mtcp\_wrappers=true
- C. edit /etc/inetd.conf and add a tcp wrapper to each enabled service
- D. edit /etc/init.d/inetsvc and add the -t option to the inetd invocation

**Answer: A**