

T estpassport問題集



更に上のクオリティ 更に上のサービス

一年で無料進級することに提供する
[Http://www.testpassport.jp](http://www.testpassport.jp)

Exam : **300-460**

Title : Implementing and
Troubleshooting the Cisco
Cloud Infrastructure

Version : DEMO

1. Which four issues are often detected when validating workflows in Cisco UCS Director? (Choose four.)

- A. Task Handler not found
- B. missing admin/task inputs after import or upgrade
- C. mapping mismatch
- D. version incompatibilities
- E. debugging logging information
- F. missing optional values for tasks
- G. missing task action value
- H. missing mandatory values for tasks

Answer: A,B,C,H

Explanation: Section Workflow validation of the link:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-director/orchestrationguide/5-4/b_UCS_Director_Orchestration_Guide_5_4/b_UCS_Director_Orchestration_Guide_5_4_chapter_011.html

2. Refer to the exhibit.

Fabric ID: B									
Path ID: 1									
VIF	vNIC	Link State	Oper State	Prot State	Prot Role	Admin Pin	Oper Pin	Transport	
755	eth0	Up	Active	Passive	Backup	0/0	0/0	Ether	
758	eth2	Up	Active	Active	Backup	0/0	0/11	Ether	
800	eth3	Up	Active	Active	Primary	0/0	0/8	Ether	
802	eth1	Up	Active	No protection	Unprotected	0/0	0/1	Ether	
806	fc1	Up	Active	No protection	Unprotected	0/0	2/1	Fc	
8997		Error	Error			0/0	0/0	Ether	
9303	1	Up	Active	No protection	Unprotected	0/0	0/0	Ether	

Cisco UCS Fabric interconnect A and B have identical uplink configurations. Which option describes the problem of Fabric interconnect A?

- A. Ethernet0/11 on Fabric interconnect A is down.
- B. The IOM on Fabric interconnect A was rebooted.
- C. FC2/1 on Fabric interconnect A is unplugged or has been replaced with a GLC-T.
- D. Fabric interconnect A is powered off.

Answer: C

3. Which option lists the number of segments that are supported by VxLAN as standardized in RFC7348 and the number of bytes of overhead that are added to the original frame?

- A. 1 million; 50
- B. 16 million; 50
- C. 1 million; 48
- D. 6 million; 50

Answer: B

Explanation: <https://tools.ietf.org/html/rfc7348>

4. A Cisco UCSM administrator has been tasked with deploying a new data center. Which two recommendations aid in the ability to associate a service with a server? (Choose two.)

- A. The host control setting for a QoS policy applies to vNICs only. It has no effect on a vHBA.
- B. You can assign only a QoS policy to a vHBA if the priority setting for that policy is set to fc, which represents the Fibre Channel system class.
- C. The host control setting for a QoS policy applies to vHBAs only.
- D. Power capping is supported for rack servers. If you include a power control policy in a service profile that is associated with a rack-mount server, the policy is implemented.

Answer: B,D

5. Where does performance tuning of high CPU utilization take place in Cisco UCS?

- A. high performance policy
- B. energy performance mode policy
- C. compute policy
- D. BIOS policy

Answer: D