TESTPASSPORT

練 習 問 題



高 品 質 な 学 習 リ ソ ー ス

https://www.testpassport.jp

1年間無料アップデート

Exam : **7595X**

Title : Avaya Surge™ Solution Integration Exam

Version : DEMO

1.To deploy an Avaya Surge™ IoT solution onto a traditional IP network, with which two static VLAN parameters would the access layer switch ports be configured? (Choose two.)
A. Tagged traffic for IoT device traffic
B. Untagall traffic for IoT device traffic
C. Untagged traffic for ONA management
D. Tagged traffic for ONA management
Answer: AC
Explanation:
https://www.avaya.com/en/documents/surge_technical_brief_dn7946.pdf?t=0

2.Which administration view provides information about invalid and active ONAs connected to the network through the Avaya Surge™ Administration user interface?
A. ONA Diagnostics port-let
B. Service Availability port-let
C. Device Inventory port-let
D. Server Status port-let
Answer: C

3.Once the authentication information for the Hyper-Sec Gateway is provided through the onboarding workflow, when will the HyperSec Gateway be in the Onboarded state?
A. When HyperSec Gateway is onboarded and discovered
B. When HyperSec Gateway is rebooted and rediscovered
C. When the HyperSec Gateway Is onboarded before discovery
D. When the HyperSec Gateway is discovered
Answer: A

4.When the status of the ONA device state is in the Inactive state, which two tasks should you perform? (Choose two.)
A. Apply service profile whitelists.
B. Insure that the IoT device is connected to the ONA.
C. Check the ONA LED to make sure it is solid green.
D. Insure that the IoT Controller has connectivity to the ONA.
Answer: AB

5.Which Avaya Surge™ Administration user interface sub interface can be used to perform the software upgrades for ONA and HyperSec Gateway?
A. ONA/HyperSec Device Diagnostics user interface
B. Surge Administration user interface
C. SDN Controller Device Orchestration user interface
D. Device Software Management
Answer: D