

# T estpassport問題集



---

更に上のクオリティ      更に上のサービス

一年で無料進級することに提供する  
[Http://www.testpassport.jp](http://www.testpassport.jp)

**Exam** : **BCP-520**

**Title** : Integrating the BlackBerry  
MVS Solution

**Version** : Demo

1.What happens during an active BlackBerry MVS call when a failover is initiated by the BlackBerry MVS Console? (Choose one.)

- A. Active BlackBerry MVS Wi-Fi calls are preserved
- B. Active BlackBerry MVS Voice over Mobile calls are preserved
- C. All Active BlackBerry MVS calls are dropped without notification
- D. All Active BlackBerry MVS calls are preserved
- E. All Active BlackBerry MVS calls are dropped after the notification tone

Answer: D

2.Which type of database authentication is required if BlackBerry MVS is installed on a different Microsoft Windows domain than the BlackBerry Enterprise Server? (Choose one.)

- A. Microsoft Windows authentication
- B. Microsoft SQL Server authentication
- C. Authentication set to db\_owner
- D. Trusted authentication

Answer: B

3.For BlackBerry devices that operate on GSM networks, which Voice over Mobile call direction offers optimal performance and reliability? (Choose one.)

- A. BlackBerry device-initiated
- B. SIP Line
- C. SIP Trunk
- D. PBX-initiated
- E. Voice over Wi-Fi

Answer: D

4.What are three functions of the SIP Line connection between the BlackBerry MVS Session Manager and the PBX? (Choose three.)

- A. Registering BlackBerry MVS users with the PBX
- B. Communicating Call setup messages
- C. Reporting on the health of the BlackBerry MVS Session Manager
- D. Exchanging KPML messages
- E. Performing PBX directory lookups

Answer: A,B,D

5.Which logging level in the BlackBerry Mobile Voice System Configuration tool logs the SIP messages between the BlackBerry MVS Server and PBX? (Choose one.)

- A. Info
- B. Severe
- C. Warning
- D. Finer
- E. Finest

Answer: E



- B. It compresses and encrypts all data that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the BlackBerry Router, to and from the wireless network.
  - C. It compresses and encrypts all data that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the media gateway, to and from the wireless network.
  - D. It compresses and encrypts RTP traffic that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the media gateway, to and from the wireless network.
  - E. It compresses and encrypts RTP traffic that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the BlackBerry Router, to and from the wireless network.
- Answer: B

10. An organization has a hunt group that is configured in the PBX with multiple outgoing trunks. Each trunk is assigned a unique Caller Identification Number. Where must each Caller Identification Number be added to ensure that PBX-initiated calling will work? (Choose one.)
- A. The MVS locations field in the BlackBerry MVS Console
  - B. The BlackBerry MVS Client on the BlackBerry device
  - C. The BlackBerry MVS Session Manager in the BlackBerry MVS Console
  - D. The BlackBerry MVS Telephony Connector in the BlackBerry MVS Console
- Answer: D

11. Which service book is required by the BlackBerry MVS Client to function properly? (Choose one.)
- A. Desktop [VoIP]
  - B. Desktop [MVSSIP]
  - C. Desktop [BBMVS]
  - D. Desktop [BBSIP]
- Answer: D

12. When a BlackBerry device is connected to a network, which BlackBerry MVS diagnostic tool should the BlackBerry MVS user use to determine the SSID of that network? (Choose one.)
- A. BlackBerry MVS Provisioning Report
  - B. Manage Connections Service status
  - C. BlackBerry MVS Unified Diagnostic Report
  - D. BlackBerry MVS Server MVS Session Managerlog
  - E. BlackBerry device Connection Logging
- Answer: B

13. What allows a BlackBerry device to be added as a valid BlackBerry device to a BlackBerry MVS user DN in a Cisco Unified Communications Manager environment? (Choose one.)
- A. Enabling KPML
  - B. Assigning the MVS user a 10 digit DID/DDI
  - C. Installing the COP file and rebooting the PBX
  - D. Configuring CSS for BlackBerry device-initiated calling
  - E. Setting the call direction for PBX-initiated calls in a MVS user class of service
- Answer: C

14.What allows a BlackBerry device to differentiate between an inbound call to the mobile number and an inbound call to the work number? (Choose one.)

- A. The BlackBerry MVS Client is programmed to recognize calls from a specific DID that the PBX uses to indicate an enterprise call
- B. The BlackBerry Enterprise Server notifies the BlackBerry device user with an email message
- C. An indicator is prepended to the ANI that is sent by the PBX to the BlackBerry device
- D. The BlackBerry MVS Session Manager sends a SIP message to the BlackBerry MVS client to indicate that a work call has been initiated
- E. Calls to the mobile number use a different ring sequence

Answer: A

15.For BlackBerry devices that operate on CDMA networks, which Voice over Mobile call direction offers the optimal performance and reliability? (Choose one.)

- A. BlackBerry device-initiated
- B. SIP Line
- C. SIP Trunk
- D. PBX-initiated
- E. Voice over Wi-Fi

Answer: A

16.Which BlackBerry MVS Session Manager configuration setting is required in order for BlackBerry device-initiated calling to work? (Choose one.)

- A. Configure a unique SIP IP address
- B. Configure BlackBerry MVS for High Availability
- C. Add a unique DID/DDI number to each BlackBerry MVS Session Manager
- D. Add a unique BlackBerry MVS Telephony Connector Caller Identification Number

Answer: C

17.Which three processes make use of the SIP Trunk? (Choose three.)

- A. BlackBerry MVS Client registration
- B. Mobile Call initiation using voice over mobile
- C. Mid-call features such as transfer and hold
- D. BlackBerry device-initiated call authentication
- E. Wi-Fi profile authentication

Answer: B,C,D

18.DRAG DROP

Click the Task button to open this item. Once you have completed this item and have selected Done, you may click Next to proceed to the next item.

**Match the terms with their descriptions.**  
**Note: A single term may match more than one description.**

This allows optimal performance for CDMA networks.	BlackBerry Device-initiated calling
This allows optimal performance for GSM networks.	PBX-initiated calling
This describes a scenario in which a voice mail connector is <b>NOT</b> required.	Solicited
This provides a scenario for reducing BlackBerry MVS downtime	PBX Clustering
	High Availability
	Unsolicited

Answer:

**Match the terms with their descriptions.**  
**Note: A single term may match more than one description.**

This allows optimal performance for CDMA networks.	BlackBerry Device-initiated calling
This allows optimal performance for GSM networks.	PBX-initiated calling
This describes a scenario in which a voice mail connector is <b>NOT</b> required.	Solicited
This provides a scenario for reducing BlackBerry MVS downtime	PBX Clustering
	High Availability
	Unsolicited

19. How many SIP Trunks are required in Cisco Unified Communications Manager when configuring BlackBerry MVS for high availability? (Choose one.)

- A. Two SIP Trunks are required for the two BlackBerry MVS Session Managers and one SIP Trunk for the BlackBerry MVS Console
- B. Four SIP Trunks are required for the two BlackBerry MVS Session Managers
- C. Two SIP Trunks are required between the two BlackBerry MVS Session Managers and two SIP

Trunks for the BlackBerry MVS Console

D. Two SIP Trunks are required for the two BlackBerry MVS Session Managers

Answer: D

20. On a planning call with a customer, the Windows account requirements for the BlackBerry MVS installation are discussed. The customer says that the BlackBerry MVS account sounds similar to the BlackBerry Enterprise Server ESAdmin account. The customer asks if this account can be used for BlackBerry MVS. What is the appropriate response to this query? (Choose one.)

A. This account can be used since it meets the requirements of the Windows account for BlackBerry MVS.

B. This account cannot be used at the risk of causing issues with the BlackBerry Enterprise Server.

C. The permissions appear similar but are not. The BESAdmin account cannot be used.

D. The BESAdmin account must be used since the BlackBerry MVS installation sets up the connection to the BlackBerry Enterprise Server.

Answer: A