

T estpassport問題集



更に上のクオリティ 更に上のサービス

一年で無料進級することに提供する
[Http://www.testpassport.jp](http://www.testpassport.jp)

Exam : NS0-160

**Title : NetApp Certified Data
Administrator, ONTAP**

Version : DEMO

1.Click the Exhibit button.

Platform Mixing Rules			
Platform Model	Maximum Nodes (NAS) [1]	Maximum Nodes (SAN) [1]	Min ONTAP Version for Platform Mixing
Fabric Attached Storage – Current Models			
FAS2620	24 Nodes	12 Nodes	9.3
FAS2650	24 Nodes	12 Nodes	9.3
FAS8200	24 Nodes	12 Nodes	9.3
FAS9000	24 Nodes	12 Nodes	9.3
All Flash FAS – Current Models			
Fabric Attached Storage – Legacy EOA Models			
FAS2520	4 Nodes	4 Nodes	9.3
FAS2552	8 Nodes	8 Nodes	9.3
FAS2554	8 Nodes	8 Nodes	9.3
FAS8020	24 Nodes	12 Nodes	9.3
FAS8040	24 Nodes	12 Nodes	9.3
FAS8060	24 Nodes	12 Nodes	9.3
FAS8080 EX	24 Nodes	12 Nodes	9.3
All Flash FAS – Legacy EOA Models			
Footnotes			
Notes ID	Notes Description		
1	Maximum number of nodes within a cluster is determined by platform which supports the fewest number of nodes.		

A storage administrator has an existing FAS2554 HA pair. They want to add a new FAS2620 HA pair to the cluster. The SAN protocols are licensed.

Referring to the exhibit, after adding the second HA pair, how many more nodes are available to add for future use?

- A. 4
- B. 12
- C. 8
- D. 2

Answer: B

2.When a write from a SAN host is received, the information is stored within the controller before it is written to the underlying RAID. In this scenario, which component stores the data?

- A. HBA
- B. FlashCache
- C. Flash Pool
- D. NVRAM

Answer: D

3.An administrator notices that the applications are running slowly. The administrator wants to determine

which component on the ONTAP subsystem is experiencing the most latency.

In this scenario, which command would you use to accomplish this task?

- A. run -node * stats show system::sys_avg_latency
- B. statistics system show
- C. run -node * -command sysstat -x 1
- D. qos statistics latency show

Answer: D

Explanation:

Reference: https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-cmpr-940%2Fqos__statistics__volume__latency__show.html

4.A customer has four or more nodes in a cluster. More than four target ports are being used by the SVMs in any node. The customer wants to limit the number of paths that can be used to access LUNs on the nodes, so that the paths do not exceed the recommended maximum of eight.

In this scenario, which three actions will accomplish this task? (Choose three.)

- A. Use ALUA protocol.
- B. Use multipathing software.
- C. Use port sets for iSCSI.
- D. Use Selective LUN Mapping
- E. Use FC switch zoning.

Answer: CDE

Explanation:

Reference: <https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-sanconf%2FGUID-133F725D-6EE4-4ACF-8352-73E731B7CFD9.html>

5.A customer configured CIFS in an ONTAP 9.5 SVM. The customer wants to verify if the “CIFS Server” is accessible from each node of the cluster.

In this scenario, which command will accomplish this task?

- A. vserver cifs session
- B. vserver cifs connection show
- C. vserver cifs check
- D. vserver cifs domain discovered-servers

Answer: C

Explanation:

Reference: https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-cmpr-950%2Fvserver__cifs__check.html