

T estpassport問題集



更に上のクオリティ 更に上のサービス

一年で無料進級することに提供する
[Http://www.testpassport.jp](http://www.testpassport.jp)

Exam : **NS0-505**

Title : NetApp Certified
Implementation Engineer –
SAN ESeries

Version : DEMO

1.Which item can be downloaded concurrently with controller firmware? (Choose the best answer.)

- A. SANtricity software
- B. NVSRAM
- C. ESM firmware
- D. Drive firmware

Answer: B

2.What should you do to confirm a component failure prior to replacing hardware? (Choose the best answer.)

- A. Run the Recovery Guru
- B. Run chkdsk on the client
- C. Check the Major Events Log
- D. Power cycle the storage array

Answer: A

3.When you arrive on a customer site, you discover that the customer network administrator has called in sick. While required power has been provided and all of the components ordered have been physically accounted for, the network will not be operational today. Which would be the most useful tool to complete your rack & stack and initial configuration of the system? (Choose the best answer.)

- A. a Serial Port cable
- B. a CD containing the 10.86 version of SANtricity
- C. a standalone switch or hub
- D. None of the above, come back tomorrow.

Answer: B

4.Consult the _____ to determine the current link status of a host port. (Choose the best answer.)

- A. Storage Array Profile
- B. Real-time performance monitor
- C. Recovery Guru
- D. Unreadable Sectorslog

Answer: A

Explanation:http://mysupport.netapp.com/NOW/public/eseries/amw/index.html#page/SANtricity_v11.20_Array_Management_Window_Help/sarray_profile.html#

5.What is SMAgent? (Choose the best answer.)

- A. a host server process that enables storage system management with the storage data path
- B. an OS-dependent collection of utilities for servers attached to SANtricity-managed storage systems
- C. a GUI or CLI run on a host server used for storage system management
- D. a host I/O performance modeling interface
- E. inter-process communication that supports computer program subroutines

Answer: A

Explanation:

The host adapters in the hosts that are attached to the storage array are known to the storage management software. However, in most cases the storage management software does not know which

host adapters are associated with which hosts. Only when the SMagent services runs on the host that is attached to a storage array can the storage management software associate HBA ports to that host.